

User Manual 3.4.1 Trigonometric Polynomials and Fourier Series

De Wiki

Aller à : [navigation](#), [rechercher](#)

[User Manual 3.4.1 Trigonometric Polynomials and Fourier Series](#)

Introduction

Scope

This section presents the Trigonometric Polynomials implemented in PATRIUS as well as Fourier Series.

Javadoc

The trigonometric polynomial (and related) objects are available in the package `org.commons.math3.analysis.polynomials` in the Commons Math Library (and Commons Math add-ons) and the FFT algorithms in `org.commons.math3.transform`

Library

Commons Math add-ons [Package org.commons.math3.geometry.analysis.polynomials](#)

Commons Math [Package org.commons.math3.transform](#)

Javadoc

Links

Useful resources for this theme can be found here :

- [Trigonometric Polynomials](#)
- [List of trigonometric identities](#)
- [Fourier Series](#)

Useful Documents

[Modèle:SpecialInclusion prefix=\\$theme sub_section="UsefulDocs"/](#)

Package Overview



Features Description

Trigonometric Polynomials

The trigonometric polynomials are defined as :

$$\text{[math]} \forall t \in \mathbb{R}, P(t) = a_0 + \sum_{k=0}^n \left(a_k \cos(kt) + b_k \sin(kt) \right) \text{[/math]}$$

And the primitive of such a function is :

$$\forall t \in \mathbb{R}, P(t) = a_0 + \sum_{k=0}^n \left(\frac{-b_k}{k} \cos(kt) + \frac{a_k}{k} \sin(kt) \right)$$

Classes that represent these functions are described in this section.

Fourier Series

Let f be a periodic, real variable, real function with period T . The *partial sums of the Fourier Series* of f are given by

$$\forall N \in \mathbb{R}^{+}, S_N(x) = a_0 + \sum_{n=1}^N \left(a_n \cos\left(\frac{n\pi}{T}x\right) + b_n \sin\left(\frac{n\pi}{T}x\right) \right)$$

The Fourier coefficients ($n > 0$) of f are given by :

$$a_0 = \frac{1}{T} \int_{-T/2}^{T/2} f(t) dt$$

$$a_n = \frac{2}{T} \int_{-T/2}^{T/2} f(t) \cos\left(\frac{n\pi}{T}t\right) dt$$

$$b_n = \frac{2}{T} \int_{-T/2}^{T/2} f(t) \sin\left(\frac{n\pi}{T}t\right) dt$$

Classes that allow decomposing functions into finite Fourier series are described.

Fast Fourier Transforms

A fast Fourier transform (FFT) is an algorithm to compute the discrete Fourier transform (DFT) and its inverse. Fourier analysis converts time (or space) to frequency and vice versa. An FFT rapidly computes such transformations by factorizing the DFT matrix into a product of sparse (mostly zero) factors.

Let (X_0, \dots, X_{N-1}) be complex numbers. The DFT is defined by the formula

$$X_k = \sum_{n=0}^{N-1} x_n e^{-2\pi i n k / N}, \quad k \in \{0, \dots, N-1\}$$

The class `FastFourierTransformer.java` owns two methods

```
transform(final double[] f, final TransformType type)
transform(final Complex[] f, final TransformType type)
```

where `TransformType` is an enumeration that defines the type of transform which is to be computed. It can be FORWARD or INVERSE.

Depending on the size, this method will use a radix-2 algorithm if the size is a power-of-two, and the Bluestein algorithm otherwise. Both algorithms are explained above.

The Cooley-Tukey & radix-2 the algorithm

By far the most commonly used FFT algorithm. This is a divide and conquer algorithm that recursively breaks down a DFT of any composite size $N = N_1 N_2$ into many smaller DFTs of sizes N_1 and N_2 , along with $O(N)$ multiplications by complex roots of unity.

The radix-2 algorithm is the most common use of FFT algorithm and is based on the Cooley-Tukey algorithm. It divides the transform into two pieces of size $N/2$ at each step, and is therefore limited to power-of-two sizes.

The Bluestein algorithm

It is commonly called the chirp z-transform algorithm. It computes the discrete Fourier transform (DFT) of arbitrary sizes (including prime sizes) by re-expressing the DFT as a convolution. For more information, see [\[1\]](#)

Getting Started

Usage of a trigonometric polynomial

- To create the polynomial $P(x) = -2 + \cos(x) + 2\sin(3x)$, use the following code snippet :

```
double a0 = -2;
double[] a = new double[] {1, 0, 0};
double[] b = new double[] {0, 0, 2};
TrigonometricPolynomialFunction myPol2 = new
TrigonometricPolynomialFunction(a0, a, b);
```

- To get the value of the second derivative at $x = 5$, use the following snippet :

```
double result = myPol2.value(2,5);
// equivalent to
double result = myPol2.polynomialDerivative(2).value(5);
```

- To get the primitive :

```
// With an integration constant c = 1 :
TrigonometricPolynomialPrimitive result = myPol2.polynomialPrimitive(1.);
```

- To multiply two trigonometric polynomials $p1$ and $p2$:

```
TrigonometricPolynomialFunction result = p1.multiply(p2);
```

Decomposing a UnivariateFunction into a Fourier Series

Given a user function with period T :

```
UnivariateFunction f = new UnivariateFunction () {
    public double value(double x) {
        // ...
        return result;
    }
};
```

The user must build an instance of the FourierDecompositionEngine (using an [integrator](#)) :

```
FourierDecompositionEngine engine = new FourierDecompositionEngine(  
integrator );
```

And pass the function, period and approximation order to it.**NOTE :** It is left up to the user to make sure that the specified period is coherent with the function as no internal check is conducted.

```
engine.setOrder(10);  
engine.setFunction(f, T);
```

Then, the user can call the `decompose()` method :

```
FourierSeriesApproximation approximation = engine.decompose();  
FourierSeries fourier = approximation.getFourier();
```

Example

The following code snippet shows how to decompose a square function of period 2 to the 10th order :

```
// function definition  
UnivariateFunction function = new UnivariateFunction() {  
    public double value(final double x) {  
        final double local = x - FastMath.floor(x / 2) * 2;  
        if (local >= 1) {  
            return -1;  
        } else {  
            return 1;  
        }  
    }  
};  
  
// Engine parameters  
UnivariateIntegrator integrator = new LegendreGaussIntegrator(5, 1e-14,  
1e-14);  
FourierDecompositionEngine engine = new  
FourierDecompositionEngine(integrator);  
engine.setMaxEvals(Integer.MAX_VALUE);  
  
// decompose  
double period = 2;  
engine.setOrder(10);  
engine.setFunction(function, period);  
FourierSeriesApproximation result = engine.decompose();  
FourierSeries fourier = result.getFourier();
```

The function and its approximation are shown hereunder. The parasite undulations are known as the [Gibbs Phenomenon](#) :



Contents

Interfaces

	Interface	Summary	Javadoc
DifferentiableUnivariateFunction		Extension of UnivariateFunction representing a differentiable univariate function.	...
IntegrableUnivariateFunction		Extension of UnivariateRealFunction representing an integrable univariate function.	...
DifferentiableIntegrableUnivariateFunction		Extension of UnivariateRealFunction representing a differentiable and integrable univariate function.	...
UnivariateFunction		Interface representing an univariate function.	...
IFastFourierTransformer		Interface representing a FFT.	...

Classes

	Class	Summary	Javadoc
FourierDecompositionEngine		Decompose a UnivariateFunction as a Fourier Series using TrigonometricPolynomialFunction representation.	...
FourierSeries		This class represents a finite Fourier Series.	...
FourierSeriesApproximation		Holder for a UnivariateFunction and its FourierSeries approximation.	...
TrigonometricPolynomialFunction		This class is the Trigonometric Polynomial Function class.	...
TrigonometricPolynomialPrimitive		This class represents a Trigonometric Polynomial Primitive.	...
AbstractFastFourierTransformer		Abstract class representing a FFT.	...
FastFourierTransformer		Computes the FFT for real and complex arrays.	...

Récupérée de

«

http://patrius.cnes.fr/index.php?title=User_Manual_3.4.1_Trigonometric_Polynomials_and_Fourier_Series&oldid=1416 »

Catégorie :

- [User Manual 3.4.1 Mathematics](#)

Menu de navigation

Outils personnels

- [3.135.209.107](#)
- [Discussion avec cette adresse IP](#)

- [Créer un compte](#)
- [Se connecter](#)

Espaces de noms

- [Page](#)
- [Discussion](#)

Variantes

Affichages

- [Lire](#)
- [Voir le texte source](#)
- [Historique](#)
- [Exporter en PDF](#)

Plus

Rechercher

PATRIUS

- [Welcome](#)

Evolutions

- [Main differences between V4.15 and V4.14](#)
- [Main differences between V4.14 and V4.13](#)
- [Main differences between V4.13 and V4.12](#)
- [Main differences between V4.12 and V4.11](#)
- [Main differences between V4.11 and V4.10](#)
- [Main differences between V4.10 and V4.9](#)
- [Main differences between V4.9 and V4.8](#)
- [Main differences between V4.8 and V4.7](#)
- [Main differences between V4.7 and V4.6.1](#)
- [Main differences between V4.6.1 and V4.5.1](#)
- [Main differences between V4.5.1 and V4.4](#)
- [Main differences between V4.4 and V4.3](#)
- [Main differences between V4.3 and V4.2](#)

- [Main differences between V4.2 and V4.1.1](#)
- [Main differences between V4.1.1 and V4.1](#)
- [Main differences between V4.1 and V4.0](#)
- [Main differences between V4.0 and V3.4.1](#)

User Manual

- [User Manual 4.15](#)
- [User Manual 4.14](#)
- [User Manual 4.13](#)
- [User Manual 4.12](#)
- [User Manual 4.11](#)
- [User Manual 4.10](#)
- [User Manual 4.9](#)
- [User Manual 4.8](#)
- [User Manual 4.7](#)
- [User Manual 4.6.1](#)
- [User Manual 4.5.1](#)
- [User Manual 4.4](#)
- [User Manual 4.3](#)
- [User Manual 4.2](#)
- [User Manual 4.1](#)
- [User Manual 4.0](#)
- [User Manual 3.4.1](#)
- [User Manual 3.3](#)

Tutorials

- [Tutorials 4.15](#)
- [Tutorials 4.14](#)
- [Tutorials 4.13.5](#)
- [Tutorials 4.12.1](#)
- [Tutorials 4.8.1](#)
- [Tutorials 4.5.1](#)
- [Tutorials 4.4](#)
- [Tutorials 4.1](#)
- [Tutorials 4.0](#)

Links

- [CNES freeware server](#)

Navigation

- [Accueil](#)
- [Modifications récentes](#)
- [Page au hasard](#)

- [Aide](#)

Outils

- [Pages liées](#)
- [Suivi des pages liées](#)
- [Pages spéciales](#)
- [Adresse de cette version](#)
- [Information sur la page](#)
- [Citer cette page](#)

- Dernière modification de cette page le 5 mars 2018 à 09:14.

- [Politique de confidentialité](#)
- [À propos de Wiki](#)
- [Avertissements](#)

